productinformation

tesa® 51025 PV10

Handtearable PET cloth tape for basic bundling

tesa® 51025 PV10 is a PET cloth wire harness tape with a solvent-free rubber based adhesive.

Major Features:

- Temperature resistance 125°C/3000h
- Solvent-free adhesive
- Handtearable

Color: Black

Main Application

tesa® 51025 PV10 is designed for the passenger compartment for basic bundling up to a temperature of 125°C.

Technical Data

Backing material	PET cloth		Temperature resistance (3000h)	125 °C
Total thickness	160 μm	•	Abrasion resistance (10mm	Class B (acc. to
Type of adhesive	rubber based		mandrel)	LV312)
Adhesion to steel	6.5 N/cm		Abrasion resistance (5mm	Class A (acc. to
Elongation at break	25 %		mandrel)	LV312)
Tensile strength	80 N/cm		Flame resistance as composite	Class B (acc. to
Temperature resistance min.	-40 °C			LV312)
			Unwind force (roll width ≤ 9mm)	8 N/roll (30 m/min)
			Unwind force (roll width > 9mm)	8 N/roll (30 m/min)
			Noise damping (decibel)	Class A (acc. to

Additional Information

Standard widths: 9, 19, 25, 32, 38 mm Standard lengths: 25, 50 m

- Most combinations of width and length are possible
- Further dimensions are available upon request
- Standard core diameter: 38 mm

Page 1 of 1 - As of 22/04/2016 - e

For latest information on this product please visit http://l.tesa.com/?ip=51025

LV312)